

**KNOBBE, MARTENS, OLSON & BEAR**A LIMITED LIABILITY PARTNERSHIP INCLUDING  
PROFESSIONAL CORPORATIONS**PATENT, TRADEMARK AND COPYRIGHT CAUSES**

620 NEWPORT CENTER DRIVE

SIXTEENTH FLOOR

NEWPORT BEACH, CALIFORNIA 92660-8016

(949) 760-0404

FAX (949) 760-9502

INTERNET. WWW.KNOB.COM

LOUIS J. KNOBBE\*  
DON W. MARTENS\*  
GORDON H. OLSON\*\*  
JAMES B. BEAR  
DARRELL L. OLSON\*  
WILLIAM B. BUNKER  
WILLIAM H. NIEMAN  
LOWELL ANDERSON  
ARTHUR S. ROSE†  
JAMES F. LESNIAK  
NED A. ISRAELSEN  
DREW S. HAMILTON  
JERRY T. SEWELL  
JOHN B. SGANGA, JR.  
EDWARD A. SCHLATTER  
GERARD VON HOFFMANN  
JOSEPH R. RE  
CATHERINE J. HOLLAND  
JOHN M. CARSON  
KAREN VOGEL WEIL†  
ANDREW H. SIMPSON  
JEFFREY L. VAN HOOSEAR  
DANIEL E. ALTMAN  
ERNEST A. BEUTLER  
MARGUERITE L. GUNN  
STEPHEN C. JENSEN  
VITO A. CANUSO III  
WILLIAM H. SHREVE  
LYNDA J. ZADRA-SYMEST†  
STEVEN J. NATAUPOSKY

PAUL A. STEWART  
JOSEPH F. JENNINGS  
CRAIG S. SUMMERS  
ANNEMARIE KAISER  
BRENTON R. BABCOCK†  
THOMAS F. SMEGAL, JR.  
MICHAEL H. TRENHOLM  
DIANE M. REED  
JONATHAN A. BARNEY  
RONALD J. SCHOENBAUM  
JOHN R. KING  
FREDERICK S. BERRETTA  
NANCY WAYS VENSKE  
JOHN P. GIEZENTANNER  
ADEEL S. AKHTAR  
RICHARD C. GILMORE  
THOMAS R. ARNO  
DAVID N. WEISS  
DANIEL HART  
JAMES T. HAGLER  
DOUGLAS G. MUEHLHAUSER  
LORI L. YAMATO  
STEPHEN M. LOBBIN  
ANN A. BYUN  
ROBERT F. GAZDZINSKI  
FRED C. HERNANDEZ  
STACEY R. HALPERN†  
MICHAEL K. FRIEDLAND  
DALE C. HUNT  
LEE W. HENDERSON

DEBORAH S. SHEPHERD  
RICHARD E. CAMPBELL  
MARK M. ABUMERI  
JON W. GURKA  
KATHERINE W. WHITE  
JOSEPH J. BASISTA  
ERIC M. NELSON  
ALEXANDER C. CHEN  
MARK R. BENEDICT  
PAUL N. CONOVER  
JOHN P. MUSONE  
ROBERT J. ROBY  
SABING H. LEE  
KAROLINE A. DELANEY  
JOHN W. HOLCOMB  
JAMES J. MULLEN, III  
JOSEPH S. CIANFRANI  
JOSEPH M. REISMAN  
WILLIAM R. ZIMMERMAN  
GLEN L. NUTTALL  
ERIC S. FURMAN  
DO TE KIM  
TIRZAH ABE LOWE  
GEOFFREY Y. IIDA  
ALEXANDER S. FRANCO  
SANJIVPAL S. GILL  
SUSAN M. MOSS  
GUY PERRY

OF COUNSEL  
JERRY R. SEILER

JAPANESE PATENT ATTY  
KATSUHIRO ARAI\*\*

EUROPEAN PATENT ATTY  
MARTIN HELLEBRANDT

KOREAN PATENT ATTY  
MINCHEOL KIM

SCIENTISTS & ENGINEERS  
(NON-LAWYERS)

RAIMOND J. SALENIEKS\*\*  
MICHAEL L. FULLER\*\*  
NEIL S. BARTFELD\*\*  
DANIEL E. JOHNSON\*\*  
JEFFERY KOEPKE  
KHURRAM RAHMAN  
JENNIFER A. HAYNES  
BRENDAN P. O'NEILL  
MARRINA Q. MEI  
THOMAS Y. NAGATA  
JOHN M. GROVER\*\*  
ALAN C. GORDON  
PETER M. MIDGLEY  
IRFAN A. LATEEF  
AMY C. CHRISTENSEN  
SHEILA N. SWAROOP

Assistant Commissioner for Patents  
Washington, D.C. 20231

**CERTIFICATE OF MAILING BY "EXPRESS MAIL"**

**Attorney Docket No. :** MPATENT.053A

**Applicant(s) :** Dean A. Klein

**For :** DATA SECURITY FOR DIGITAL DATA STORAGE

**Attorney :** Thomas R. Arno

**"Express Mail"**

**Mailing Label No. :** EL327883285US

**Date of Deposit :** March 26, 1999

I hereby certify that the accompanying

Transmittal in Duplicate; Specification in 14 pages; 4 sheets of drawings; Return  
Prepaid Postcard

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and are addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

John J. Riedel

S:\DOCS\TRA\TRA-2189.DOC  
032699

ASSISTANT COMMISSIONER FOR PATENTS  
WASHINGTON, D.C. 20231  
ATTENTION: APPLICATION BRANCH

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): **Dean A. Klein**

For: **DATA SECURITY FOR DIGITAL DATA STORAGE**


Enclosed are:

(X) Four (4) sheet(s) of drawings.

(X) Return prepaid postcard.

CLAIMS AS FILED

FOR	NUMBER FILED	NUMBER EXTRA	RATE	FEE
Basic Fee			\$760	\$760
Total Claims	12 - 20 =	0 ×	\$18	\$0
Independent Claims	3 - 3 =	0 ×	\$78	\$0
If application contains any multiple dependent claims(s), then add			\$260	\$0
FILING FEE TO BE PAID AT A LATER DATE		\$760		

  
Thomas R. Arno  
Registration No. 40,490  
Attorney of Record

S:\DOCS\TRA\TRA-2187.DOC  
032699

**DATA SECURITY FOR DIGITAL DATA STORAGE**Background of the InventionField of the Invention

5           The invention relates to methods and apparatus for providing security for digital data stored on data storage media such as magnetic and optical disks and tapes.

Description of the Related Art

10           Over the past several years, personal computing systems have become more powerful, smaller, and less expensive. As this has occurred, more and more computing applications are performed on personal computer platforms. Local and wide area networks of personal computers are now often used in corporate and business applications instead of the large mainframes used for the same applications in the past. A further result of the increases in performance and decreases in price of personal computers is a dramatic increase in personal computer use for household financial and  
15           other sensitive and preferably confidential information.

          The use of personal computers in these applications raises data security and privacy issues which have thus far been insufficiently resolved. Laptop and other personal computers, as well as the removable data storage media used in them are transported, mislaid, lost, and sometimes stolen. Consequently, security and privacy  
20           issues which were not present when computers and their data storage media were generally fixed have now become prominent. Administrators of computer resources in the business environment must remain aware of the location of portable computing devices as well as the nature of the programs and data stored on them. For home users, concerns arise if credit card, social security, or bank account numbers are present on  
25           fixed or removable media which may be lost or stolen.

          To resolve a few of these concerns, some programs allow the user to password protect documents or files, thereby preventing access to the data in the file unless the password is known. This provides limited security, however, since these schemes are easy to defeat with widely available password extraction programs. Furthermore,  
30           although the act of opening the file may be restricted in the relevant application

program, the data itself resides on the media in raw form, and may still be extracted by a trained computer user.

Systems have also been proposed which perform encryption on data and application programs stored on tape and disk. These systems provide improved security over the password protection described above. As one example, a system disclosed in U.S. Patent No. 5,325,430 to Smyth et al. (incorporated herein by reference in its entirety) includes a security module attached to a personal computer which performs data and application program encryption. The security module communicates with a removable smart card assigned to a given user which contains encryption keys used by the security module. Although the security provided by this system is adequate for many applications, the circuitry used to implement the system is complex, and administration of the system for producing and assigning keys and smart cards is time consuming and expensive.

Another system for encrypting files is disclosed in U.S. Patent No. 5,235,641 to Nozawa et al., the disclosure of which is also incorporated herein by reference in its entirety. In this system, data stored to a magnetic tape is encrypted by a cryptographic adapter which is located in the data path between a host processor and a tape drive. In this system, the host processor generates cryptographic keys which are stored on the tape itself. This requires additional logic to encrypt the keys as well as the data, and consequently, this system requires relatively complex circuitry, and leaves the key potentially recoverable from the tape itself if the key encryption scheme is broken.

Thus, existing encryption systems for personal and portable computers have serious drawbacks, and have not been widely implemented. In particular, a system which is useful for an individual personal computer user has not been heretofore provided. Such a system should provide data security with flexibility and without expensive administration or implementation.

#### Summary of the Invention

In a computer system comprising host computing logic and at least one data storage device, the invention comprises a method of data storage comprising encrypting user generated data with an encryption process, wherein said encryption process is

defined at least in part with information assigned to and associated with said host computing logic.

The invention may also comprise methods of making a computer. In one embodiment, such a method comprises storing a hardware identifier in a non-volatile memory integrated circuit and installing the memory integrated circuit into said computer. The method may further comprise providing a data path to data storage media, coupling a logic circuit comprising an encryption engine to the data path, and connecting the memory integrated circuit to the logic circuit.

#### Brief Description of the Drawings

FIG. 1 is a block diagram of a data storage system incorporating an embodiment of the invention.

FIG. 2 is a flow chart illustrating acts performed during key generation in an embodiment of the invention.

FIG. 3 is a block diagram illustrating an encrypting data path passing from a host processor to data storage devices, in accordance with one embodiment of the invention.

FIG. 4 is a flow chart illustrating acts performed during key generation in another embodiment of the invention.

#### Detailed Description of the Invention

Embodiments of the invention will now be described with reference to the accompanying Figures, wherein like numerals refer to like elements throughout. The terminology used in the description presented herein is not intended to be interpreted in any limited or restrictive manner, simply because it is being utilized in conjunction with a detailed description of certain specific embodiments of the invention. Furthermore, embodiments of the invention may include several novel features, no single one of which is solely responsible for its desirable attributes or which is essential to practicing the invention herein described.

Referring now to Figure 1, a data storage system is illustrated which incorporates aspects of the invention. The system includes encryption/decryption logic 10 that is connected to receive digital data from a data bus 12. The encryption/decryption logic 10 is configured to forward data received from the data bus 12 to data storage devices 14 in

an encrypted form. The data or information transferred between the data bus 12 and the data storage devices may comprise application programs themselves, data used by application programs, or any other information that the host computing system stores to the data storage devices 14 of the system. As will be further explained below with  
5 reference to Figures 2 and 3, the encryption/decryption logic may in some embodiments be configurable to perform the encryption and decryption on a selectable subset of the data storage devices if desired by a user of the system.

The algorithm used to perform the encryption may comprise any known encryption algorithm, and many different alternatives will be well known to those of skill  
10 in the art. In many applications, the encryption and decryption process will be defined in part by a key 16 which is utilized by the encryption/decryption logic 10 to perform the data manipulation which results in data encryption and decryption. In some systems, the same key is used for both the encryption and decryption processes, but in others, the key  
15 16 may comprise a pair of keys, wherein one is used for encryption, and the other for decryption. Given the variety of encryption and decryption schemes which have been and are currently being developed, the use of the word "key" is intended to encompass any piece of information, data, parameter, definition, configuration of logic circuitry, or other entity or circuit arrangement which serves at least in part to configure the encryption/decryption logic, or to otherwise in any way partly or wholly define the data  
20 encryption process which is performed by the encryption/decryption logic 10.

Also provided in the system of Figure 1 is a non-volatile memory location 18. As is well known in the art, a non-volatile memory has the property that the data or information stored in it remains when the host system is powered down. Non-volatile memory may comprise battery backed up RAM, EPROM, EEPROM, or ROM memory  
25 circuitry, for example. In the application of Figure 1, this memory location 18 may advantageously store an identification code. The stored identification code may be used to derive, at least in part, the key 16 which is used in the encryption process. This derivation may involve simply making the key the identification code itself, or may alternatively involve a logical or mathematical manipulation or transformation of the identification  
30 code to produce the key. In some embodiments, as will be further explained below, the key 16 may be derived in part from the identification code stored in the non-volatile

memory and in part from a password or other piece of information entered by a user of the computing system.

The system of Figure 1 includes many advantages over prior art data encryption schemes and is especially applicable to individual personal computer and laptop computer users. In some embodiments, the circuitry of Figure 1 may be incorporated into, for example, a laptop computer which is sold to an individual for household and/or business use. In most of these situations, the purchased computer will not be a member of a group of computers which is controlled or overseen by a system administrator that will create and assign encryption keys, smart cards, etc. Rather, the laptop will be simply used as is, for both personal and business use by a user who is generally unfamiliar with data security techniques or procedures.

In these embodiments, the identification code may comprise a multi-bit data word which is associated with the individual laptop being used. When stored in a non-erasable memory element such as ROM or EPROM, the identification code may be substantially permanently associated with the individual laptop being used. It will be appreciated that data security in these environments is enhanced if different laptops do not typically share a common identification code. When this is true, the key derived from the identification code will be different in different laptops produced by the laptop manufacturer. It will therefore also be appreciated that the data stored on the data storage devices 14 will be encrypted differently by different laptops. Thus, a removable media such as a floppy disk, tape, or writeable CD will not be useable on any computer except the one that originally stored the data. Thus, a level of security is provided for removable media which may be lost, mislaid, or stolen.

It will also be appreciated that this level of security is provided without any intervention by the user or a system administrator. Key generation and data encryption is automatic and transparent. In addition, this data security scheme is easily implemented in the large scale production of laptops and other personal computers. Machine specific data encryption may be provided with the simple provision of non-volatile storage of information which defines the data encryption process performed. This information may advantageously be substantially uniquely associated with the host computing logic or host computer. This may be ensured by using some form of sequential numbering

5 scheme for the identification code, or alternatively a random or pseudo-random numbering scheme with a low probability of producing two identical identification codes for different laptops. However, it may be noted that it is not necessary to absolutely guarantee that each laptop have a uniquely defined encryption process. The desirable feature is that there be a relatively low probability that lost or stolen media will be readable in some other laptop or personal computer available to someone who has found or has stolen the media elements. Therefore, duplicate identification codes and keys defining identical encryption processes may be provided within a given set of computers while still maintaining a useful level of security. Thus, the association  
10 between identification codes and their respective host computers need only be substantially unique such that a reasonable level of security is created.

Figure 2 illustrates a method of key generation and data encryption according to one embodiment of the invention. It will be appreciated that the method shown in Figure 2 may, in one embodiment, be implemented on hardware illustrated in Figure 1.

15 The method begins at a start state 22, and moves from there to step 24, where an identification code is retrieved. The identification code may be stored in a non-volatile memory, and may in addition be substantially uniquely associated with specific host computer hardware.

The system then moves to decision state 26, where it is decided whether or not  
20 some user input should be utilized in the process of encryption key generation. If not, the method moves directly to step 28, where an encryption key is generated using the identification code retrieved at step 24. If user input is to be used in key generation, the method moves from step 26 to step 30, where the user input is accepted by the system. The user input may, for example, comprise an alphanumeric code which is typed into the  
25 computer keyboard by the user in response to a system prompt. Following this, the method moves to step 28, where the key is generated using both the identification code and the user input. The user input from step 30 may be an alphanumeric sequence which is converted to a multi-bit word (for example, to ASCII code). This word may be combined with the identification code in many ways, including concatenation as one  
30 simple example, or other more complicated logical or mathematical manipulations may be used.



Following key generation at step 28, the key is used to encrypt and decrypt data that is stored to and retrieved from a data storage device at step 32. In the personal computer or laptop computer context, the series of steps leading to and including key generation may be performed during the boot operation prior to any accesses to encrypted data storage devices. In these embodiments, all data, programs, etc. stored on the data storage devices are encrypted with the same key, a key which may require some user input to generate as described above. The computer may be either factory configured or user configured to require or not require user input for key generation.

The addition of user input to key generation provides an enhancement to data security beyond that provided when only the identification code is used to derive an encryption key. This is because if the entire computer is lost or stolen, when the computer is turned on only the computer owner will know what code or password to input in order to generate the proper key at step 28 of Figure 2. Thus, access to encrypted programs and data is effectively prevented even with the original computer the hands of an unauthorized user.

An embodiment of the invention is also illustrated in Figure 3 which may be used to implement the process described above with reference to Figure 2. In this Figure, a computer system is shown having a host processor 36, which may, for example, comprise a member of the Pentium® family of processors such as the Pentium, Pentium Pro, or Pentium II. Although industry standard PC architecture is used as an illustrative example in this Figure, it will be appreciated that many computer designs may be implemented using the principles illustrated herein. Also provided as part of the computer system of Figure 3 are a plurality of data storage devices, including hard disk drives 38, 40, a floppy disk drive 42 and a CD drive 46, which may be of a writeable type.

The processor 36 interfaces with a host bus 44 which also interfaces with a bridge circuit 46. The bridge circuit 46 routes data from the host bus 44 to a PCI bus 48. The PCI bus 48 provides a data source to a logic circuit 50 which is provided in the data path between the PCI bus 48 and an IDE bus 52 and floppy drive control bus 54 which interface directly with the respective data storage devices 38, 40, 42, 44, and 46. The PCI bus 48 may also receive data from I/O devices 56 via a PCI to ISA bridge circuit 58.

The logic circuit 50 advantageously includes an encryption engine 60 which

operates to encrypt data routed to one or more of the data storage devices 38, 40, 42, 46 and to decrypt data routed from one or more of the data storage devices 38, 40, 42, 46. The logic circuit 50 will also generally include input and output bridge circuitry 51 to buffer data and convert the data transfer protocol from the PCI format bus 48 to the busses 52, 54, which interface directly with the data storage devices 38, 40, 42, 46.

The encryption engine operates under the control of control logic 62. The control logic, in turn, receives information for controlling the encryption engine from three sources. The first is a memory location which stores a hardware identifier 64. As described above, this hardware identifier 64 may be substantially uniquely associated with the computer hardware. The memory may comprise a non-volatile writeable or read only memory to help ensure essentially permanent storage of the hardware identifier 64. As is also described above, the hardware identifier 64 stored in the memory may be used by the control logic 62 (or alternatively the processor 36) to at least in part derive a key for encryption and decryption of data to and from the data storage devices 38, 40, 42, 46. The control logic may also accept user input as described above to be used as additional information for key derivation.

This generated key may be stored in a key register 66 which also is coupled to the control logic 62. Prior to data being stored or retrieved from the data storage devices 38, 40, 42, 46, the key may be retrieved from the key register 66 for use by the encryption engine 60 during the encryption and decryption processes.

A configuration register 70 may also be coupled to the control logic 62. The content of the configuration register 70 may advantageously be user defined, and may include bits that determine which of the data storage devices 38, 40, 42, 46 have data encrypted before storage to the media, and which have data decrypted when data is retrieved from the media. This feature provides significant flexibility to the user. A user may, for example, want to encrypt some, but not all, data stored onto a floppy disk with the floppy drive 42. It may also be advantageous to have at least one hard drive 38 or 40, which contains DOS, Windows (TM), Unix (TM) or other operating system software, to remain unencrypted.

The configuration register may also contain bits which determine whether or not user input should be incorporated into the key being used to perform the encryption and

decryption. In some embodiments, a different key may be stored for different drives. In this case, some of the keys may be generated with user input, and some without.

One advantageous aspect of the encryption system described herein is that it may be created with relatively minor modifications to currently existing integrated circuits. PCI to ISA and PCI to IDE bridges are well known and understood, and are commercially available from, for example, Intel Corporation. In one embodiment, therefore, an encryption engine, control logic, a key register, and a configuration register may be incorporated into an existing bridge integrated circuit design to produce a portion of the logic circuit 50. Furthermore, individual EPROM, EEPROM and ROM memories which include pre-programmed identification codes are available commercially from Dallas Semiconductor of Dallas Texas as part numbers DS2401 and DS2430 for example. These devices include a unique 48 bit serial number in a ROM storage location which may be utilized as the memory location which stores the hardware identifier 64. These memory chips are available with a serial I/O interface for reading the identification code and any other stored data. In this embodiment, therefore, a bridge integrated circuit which includes the encryption logic may interface over a serial bus to a separate memory integrated circuit which stores the hardware identifier.

Figure 4 illustrates a method of key generation and verification which may be implemented with the system illustrated in Figure 3. In the method of Figure 4, the control logic 62 (Figure 3) may be utilized to perform key generation and verification without intervention by the processor 36 (Figure 3). The method begins at a start state 76. Following this start block 76, the system retrieves the hardware identifier 64 (Figure 3) from the non-volatile memory location where it is stored. This retrieval process may involve the sequential retrieval of a set of data words from the memory as illustrated by the loop defined by blocks 78, 80, and 82. Thus, at block 78, the control logic 62 may output an initial address to the non-volatile memory to retrieve a first data word comprising a portion of the hardware identifier code 64. The address may then be incremented at block 80. If, at decision block 82, it is determined that the entire code has not yet been retrieved, the system loops back to block 78 and outputs the incremented address to the non-volatile memory to retrieve another segment of the code.

Once the entire code has been retrieved, at block 84 the control logic 62 may then

generate and verify the key. As mentioned above, the process of key generation may involve merely storing a concatenation of the data words retrieved at steps 78-82 in the key register 66. This could occur during the retrieval process, or afterwards. Alternatively, mathematical or logical manipulations may be performed on the retrieved data words prior to their storage into the key register. Key verification may also be performed in a number of ways known to those of skill in the art. For example, a checksum or CRC field may be provided in the configuration register 70 or control logic 62. If no user input is utilized in key generation, this field may be generated during an initialization sequence performed during the manufacture of either the logic circuit 50 or a computer system that the logic circuit 50 is incorporated into. If user input is utilized in key generation, this CRC or checksum field may be generated during a password initialization routine when the password to be utilized in key generation is initially entered by the user.

Following key generation and verification, the system moves to a decision state 86, where the result of the key verification of block 84 is checked. If the key is verified as good, the system moves to block 88, and the key is used to encrypt and decrypt data during data storage and retrieval operations. There are several reasons why key verification might fail. An error in reading the hardware identifier may cause faulty key generation. Tampering with the logic circuit 50 may also result in incorrect key generation. Additionally, key verification may fail because required operator input to be used in key generation has not yet been entered by a user. Thus, a failure of key verification may force user input. This is illustrated in Figure 4 by the fact that if, at decision state 86, the key has not been verified as good, the system moves to a another decision state 90. At decision state 90, the system determines whether or not user input should be accepted and used in the key generation process. If the system determines that operator input should be accepted, the system moves to block 92, where the input is read. The system then loops back to block 84, where the key is generated using both the operator input and the retrieved identification code, and is again verified against the stored CRC or checksum field. If the operator input was the correct password, the key will be verified as good at the next iteration of decision block 86, and at block 88, the key will be used to encrypt and decrypt data as described above.

If, however, the operator input was incorrect, the key verification process will fail, and the system will again move to decision state 90, where the system again determines whether or not user input should be accepted. It will be appreciated that the user may be given two or more attempts to successfully input the proper password. Thus, the system may loop back to blocks 92 and 84 a plurality of times, any one of which may result in correct password entry and normal data encryption and decryption at block 88.

After a selected number of iterations of incorrect password entry, the system may decide at state 90 to refuse to accept further operator input for key generation. In this event, the system moves to block 94 where the key error is flagged by the system. System response to the error flag may vary widely. The system may indicate to the user that the password entries are incorrect. The system may even be programmed to destroy the content of encrypted drives in the event the key verification process fails, or fails for a selected number of consecutive verification attempts.

The encryption system described thus provides data security to personal and laptop computer users in a transparent manner without requiring time consuming and expensive system administration or complex and expensive hardware. The system is especially adapted to individual users, and the high volume production of computers for these users.

The foregoing description details certain embodiments of the invention. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the invention can be practiced in many ways. As is also stated above, it should be noted that the use of particular terminology when describing certain features or aspects of the invention should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the invention with which that terminology is associated. The scope of the invention should therefore be construed in accordance with the appended claims and any equivalents thereof.

WHAT IS CLAIMED IS:

1. In a personal computer, a method of storing data on one or more magnetic or optical data storage media in an encrypted form comprising:

5 retrieving an identification code from a non-volatile memory location in said personal computer;

generating a cryptographic key derived at least in part from said identification code;

encrypting data for storage on one of said data storage media using said cryptographic key.

10 2. The method of Claim 1, additionally comprising:

retrieving information from a memory location; and

disabling encryption of data routed to one of said data storage media in response to said information.

15 3. The method of Claim 1, wherein said retrieving is performed without intervention by a host processor.

4. The method of Claim 3, additionally comprising verifying said key, wherein said verifying occurs without intervention of said host processor.

20 5. A method of making a computer comprising:  
storing a hardware identifier in a non-volatile memory integrated circuit;  
installing said memory integrated circuit into said computer;  
providing a data path to data storage media;  
coupling a logic circuit comprising an encryption engine to said data path; and

connecting said memory integrated circuit to said logic circuit.

25 6. The method of Claim 5, wherein said act of connecting comprises routing a serial data bus from said memory integrated circuit to said logic circuit.

30 7. In a computer system comprising host computing logic and at least one data storage device, a method of data storage comprising encrypting user generated data with an encryption process, wherein said encryption process is defined at least in part with information assigned to and associated with said host computing logic.

8. The method of Claim 7, wherein said information is substantially permanently associated with said host computing logic.

9. The method of Claim 7, wherein said information comprises a multi-bit identification code.

5 10. The method of Claim 9, additionally comprising the act of deriving an encryption key at least in part from said identification code.

11. The method of Claim 10, wherein said identification code is stored in a non-volatile memory in said computer system.

10 12. The method of Claim 7, additionally comprising defining said encryption process at least in part from user input to said computer system.

continued on next page

### Abstract of the Disclosure

10

S:\DOCS\TRA\TRA-1819.DOC  
121198






FIG. 1




FIG. 2




FIG. 3

```

graph TD
    76([START]) --> 78[OUTPUT ADDRESS TO NON VOLATILE MEMORY]
    78 --> 80[INCREMENT ADDRESS]
    80 --> 82{DONE ?}
    82 -- NO --> 78
    82 -- YES --> 84[GENERATE AND VERIFY KEY]
    84 --> 86{KEY GOOD ?}
    86 -- YES --> 88[USE KEY TO ENCRYPT AND DECRYPT DATA FOR STORAGE]
    86 -- NO --> 90{ACCEPT OPERATOR INPUT ?}
    90 -- YES --> 92[READ OPERATOR INPUT]
    92 --> 84
    90 -- NO --> 94[FLAG ERROR]
    94 --> 96([END])
  
```

FIG. 4